

Trailer

- 8-in double I-beam construction with support studs on 16-in centers for added durability
- Double axle rated for 14,000 lb (6,356 kg) or 16,000 lb (7,257 kg) GVWR (Gross Vehicle Weight Rating) engineered specifically for Graco
- 48-in, 4 hinge side door, 60/40, 4 hinge split barn rear doors with hose hatch
- Epoxy floor, insulated walls, ceiling and floor
- 2 5/16-in ball receiver
- Double jack stands that are square and adjustable (28 ft trailer only); other trailers have a single crank-style jack stand
- Torsion springs, emergency brakes, spare tire, custom louvers and built in door locks
- One piece aluminum roof
- 12 volt interior lights
- Bogey wheels provide skid protection
- Backed by 5-year limited warranty

Generator

- John Deere® 4 cylinder diesel generator
- 40 kw power output
- 50 gal (189 l) integrated tank
- 12 volt battery

Compressors

Rotary screw compressor (attached to generator)

- 40 CFM with sump
- Air on demand
- Easy to maintain and get parts

Champion® brand compressed air pump system also available with base mount, horizontal and vertical configurations

- Available in 5 and 10 horsepower
- Single and two stage splash lubricated pumps
- Constant run control with head unloaders
- 5-year national service coverage

Air Dryer

- High ambient temperature air dryer
- Designed to operate in extreme environments with inlet air temperatures in excess of 225°F (107°C)
- 110 volt power
- Electrically monitors dew point and is piped to the exterior

Electrical

- 24 circuit 150 amp electrical panel
- 110 volt shore power hook up

Added Features

- Optional work bench and cabinets
- 6 drawer tool box
- Color-coded drum restraints
- Frame-mounted hose racks that hold 400 feet (121 m) of hose
- Frame-mounted transfer pump racks

